

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION
1) 2012 IRC	R304.1	<p>*Revise Section R304.1 'Minimum Area' to read as follows:</p> <p>R304.1 Minimum area. Every dwelling unit shall have at least one habitable room that shall have not less than <u>120 square feet (11 m²) of gross floor area. Habitable rooms shall have a floor area of not less than 70 square feet (6.5 m²).</u></p> <p><u>Exception: Kitchens.</u></p> <p>(Effective January 1, 2018)</p>	DCA	
2) 2012 IRC	R304.2	<p>*Delete Section R304.2 'Other rooms' entirely without substitution:</p> <p>R304.2 Other rooms. Other habitable rooms shall have a floor area of not less than 70 square feet (6.5 m²).</p> <p>Exception: Kitchens.</p> <p>Remainder of code section is unchanged.</p> <p>(Effective January 1, 2018)</p>	DCA	
3) 2012 IRC	TABLE R502.5(1)	<p>*Revise TABLE R502.5(1) 'GIRDER SPANS AND HEADER SPANS FOR EXTERIOR BEARING WALLS' to read as follows:</p> <p>TABLE R502.5(1) GIRDER SPANS AND HEADER SPANS FOR EXTERIOR BEARING WALLS (Maximum spans for Douglas fir-larch, hem-fir, southern pine and spruce-pine-fir and required number of Jack studs)</p> <p><i>Revise footnote b as follows:</i></p> <p>b. Spans are based on minimum design properties for No. 2 Grade lumber of Douglas fir-larch, hem-fir, <u>and spruce-pine-fir;</u> and No. 1 or better gGrade lumber shall be used for <u>of</u> southern pine. <u>For No. 2 Grade southern pine the allowable spans shall be multiplied by 0.93.</u></p> <p>(Effective January 1, 2018)</p>	Paul Coats AWC	
4) 2012 IRC	TABLE R502.5(2)	<p>*Revise TABLE R502.5(2) 'GIRDER SPANS AND HEADER SPANS FOR INTERIOR BEARING WALLS' as follows:</p> <p>TABLE R502.5(2) GIRDER SPANS AND HEADER SPANS FOR INTERIOR BEARING WALLS (Maximum spans for Douglas fir-larch, hem-fir, southern pine and spruce-pine-fir and required number of Jack studs)</p>	Paul Coats AWC	

*Note: These amendments are "proposed only" and have not been adopted by the Department of Community Affairs.

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION																				
		<p>Revise footnote b as follows:</p> <p>b. Spans are based on minimum design properties for No. 2 Grade lumber of Douglas fir-larch, hem-fir, and spruce-pine-fir; and No. 1 or better Grade <u>Grade</u> lumber shall be used for <u>of</u> southern pine. <u>For No. 2 Grade southern pine the allowable spans shall be multiplied by 0.93.</u></p> <p>(Effective January 1, 2018)</p>																						
5) 2012 IRC	TABLE R703.4	<p>*Revise Table R703.4 TIE ATTACHMENT AND AIRSPACE REQUIREMENTS to read as follows:</p> <p style="text-align: center;">TABLE R703.7.4 TIE ATTACHMENT AND AIRSPACE REQUIREMENTS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">BACKING AND TIE</th> <th style="width: 25%;">MINIMUM TIE</th> <th style="width: 25%;">MINIMUM TIE FASTENER ^a</th> <th colspan="2" style="width: 25%;">AIRSPACE ^c</th> </tr> </thead> <tbody> <tr> <td>Wood stud backing with corrugated sheet metal</td> <td>22 U.S. gage (0.0299 in.) x 7/8 in. wide</td> <td>8d common nail ^b (2 ½ in. x 0.131 in.)</td> <td colspan="2">Nominal 1 in. between sheathing and veneer</td> </tr> <tr> <td>Wood stud backing with metal strand wire</td> <td>W1.7 (No. 9 U.S. gage; 0.148 in.) with hook embedded in mortar joint</td> <td>8d common nail ^b (2 ½ in. x 0.131 in.)</td> <td>Minimum nominal 1 in. between sheathing and veneer</td> <td>Maximum 4 ½ in. between backing and veneer</td> </tr> <tr> <td>Cold-formed steel stud backing with adjustable metal strand wire</td> <td>W1.7 (No. 9 U.S. gage; 0.148 in.) with hook embedded in mortar joint</td> <td>No. 10 screw extending through the steel framing a minimum of three exposed threads</td> <td>Minimum nominal 1 in. between sheathing and veneer</td> <td>Maximum 4 ½ in. between backing and veneer</td> </tr> </tbody> </table> <p>For SI: 1 inch = 25.4 mm</p> <p>a. In Seismic Design Category D₀, D₁ or D₂, the minimum tie fastener shall be an 8d ring-shank nail (2 ½ in. x 0.131 in.) or a No. 10 screw extending through the steel framing a minimum of three exposed threads.</p> <p>b. All fasteners shall have rust-inhibitive coating suitable for the installation in which they are being used, or be manufactured from material not susceptible to corrosion.</p> <p>c. <u>An airspace that provides drainage shall be permitted to contain mortar from construction.</u></p> <p>(Effective January 1, 2018)</p>	BACKING AND TIE	MINIMUM TIE	MINIMUM TIE FASTENER ^a	AIRSPACE ^c		Wood stud backing with corrugated sheet metal	22 U.S. gage (0.0299 in.) x 7/8 in. wide	8d common nail ^b (2 ½ in. x 0.131 in.)	Nominal 1 in. between sheathing and veneer		Wood stud backing with metal strand wire	W1.7 (No. 9 U.S. gage; 0.148 in.) with hook embedded in mortar joint	8d common nail ^b (2 ½ in. x 0.131 in.)	Minimum nominal 1 in. between sheathing and veneer	Maximum 4 ½ in. between backing and veneer	Cold-formed steel stud backing with adjustable metal strand wire	W1.7 (No. 9 U.S. gage; 0.148 in.) with hook embedded in mortar joint	No. 10 screw extending through the steel framing a minimum of three exposed threads	Minimum nominal 1 in. between sheathing and veneer	Maximum 4 ½ in. between backing and veneer	Glen Clapper BIA	
BACKING AND TIE	MINIMUM TIE	MINIMUM TIE FASTENER ^a	AIRSPACE ^c																					
Wood stud backing with corrugated sheet metal	22 U.S. gage (0.0299 in.) x 7/8 in. wide	8d common nail ^b (2 ½ in. x 0.131 in.)	Nominal 1 in. between sheathing and veneer																					
Wood stud backing with metal strand wire	W1.7 (No. 9 U.S. gage; 0.148 in.) with hook embedded in mortar joint	8d common nail ^b (2 ½ in. x 0.131 in.)	Minimum nominal 1 in. between sheathing and veneer	Maximum 4 ½ in. between backing and veneer																				
Cold-formed steel stud backing with adjustable metal strand wire	W1.7 (No. 9 U.S. gage; 0.148 in.) with hook embedded in mortar joint	No. 10 screw extending through the steel framing a minimum of three exposed threads	Minimum nominal 1 in. between sheathing and veneer	Maximum 4 ½ in. between backing and veneer																				
6) 2012 IRC	Appendix V	<p>*Add new APPENDIX V 'TINY HOUSES' to read as follows:</p> <p style="text-align: center;"><u>APPENDIX V</u></p> <p style="text-align: center;"><u>TINY HOUSES</u></p> <p style="text-align: center;"><u>SECTION AV101 GENERAL</u></p> <p><u>AV101.1 Scope.</u> This appendix shall be applicable to tiny houses used as single dwelling units. <u>Tiny houses shall comply with this code except as otherwise stated in this appendix.</u></p>	Robert Reed Southface																					

*Note: These amendments are "proposed only" and have not been adopted by the Department of Community Affairs.

ACTION: A (Approve as Submitted); R (Approve as Revised); D (Disapprove); W (Withdrawn); CF (Carry Forward)

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION
		<p><u>APPENDIX AV102 DEFINITIONS</u></p> <p><u>AV102.1 General.</u> The following words and terms shall, for the purposes of this appendix, have the meanings shown herein. Refer to Chapter 2 of this code for general definitions.</p> <p><u>EGRESS ROOF ACCESS WINDOW.</u> A skylight or roof window designed and installed to satisfy the emergency escape and rescue opening requirements in Section R310.2.</p> <p><u>LANDING PLATFORM.</u> A landing provided as the top step of a stairway accessing a loft.</p> <p><u>LOFT.</u> A floor level located more than 30 inches (762 mm) above the main floor and open to it on at least one side with a ceiling height of a maximum of 5 feet, used as a living or sleeping space.</p> <p><u>TINY HOUSE.</u> A dwelling that is 400 square feet (37 m²) or less in floor area excluding lofts.</p> <p style="text-align: center;"><u>SECTION AV103 CEILING HEIGHT</u></p> <p><u>AV103.1 Minimum ceiling height.</u> Habitable space and hallways in tiny houses shall have a finished ceiling height of not less than 6 feet 8 inches (2032 mm). Obstructions shall not extend below these minimum ceiling heights including beams, girders, ducts, lighting and other obstructions.</p> <p style="padding-left: 40px;"><u>Exception:</u> Ceiling heights in lofts are permitted to be a maximum of 5 feet.</p> <p style="text-align: center;"><u>SECTION AV104 LOFTS</u></p> <p><u>AV104.1 Minimum loft area and dimensions.</u> Lofts used as a sleeping or living space shall meet the minimum area and dimension requirements of Sections AV104.1.1 through AV104.1.3.</p> <p><u>AV104.1.1 Minimum area.</u> Lofts shall have a floor area of not less than 35 square feet (3.25 m²).</p> <p><u>AV104.1.2 Minimum dimensions.</u> Lofts shall be not less than 5 feet (1524 mm) in any horizontal dimension.</p> <p><u>AV104.1.3 Height effect on loft area.</u> Portions of a loft with a sloping ceiling measuring less than 3 feet (914 mm) from the finished floor to the finished ceiling shall not be considered as contributing to the minimum required area for the loft.</p> <p style="padding-left: 40px;"><u>Exception:</u> Under gable roofs with a minimum slope of 6:12, portions of a loft with a sloping ceiling measuring less than 16 inches (406 mm) from the finished floor to the finished ceiling shall not be considered as contributing to the minimum required area for the loft.</p>		

*Note: These amendments are “proposed only” and have not been adopted by the Department of Community Affairs.

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION
		<p><u>AV104.2 Minimum dimensions.</u> The access to and primary egress from lofts shall be any type described in Sections AV104.2.1 through AV104.2.4.</p> <p><u>AV104.2.1 Stairways.</u> Stairways accessing lofts shall comply with this code or with Sections AV104.2.1.1 through AV104.2.5.</p> <p><u>AV104.2.1.1 Width.</u> Stairways accessing a loft shall not be less than 17 inches (432 mm) in clear width at or above the handrail. The minimum width below the handrail shall be not less than 20 inches (508 mm).</p> <p><u>AV104.2.1.2 Headroom.</u> The headroom in stairways accessing a loft shall be not less than 6 feet 2 inches (1880 mm), as measured vertically, from a sloped line connecting the tread or landing platform nosings in the middle of their width.</p> <p><u>AV104.2.1.3 Treads and risers.</u> Risers for stairs accessing a loft shall be not less than 7 inches (178 mm) and not more than 12 inches (305 mm) in height. Tread depth and riser height shall be calculated in accordance with one of the following formulas:</p> <ol style="list-style-type: none"> <u>1. The tread depth shall be 20 inches (508 mm) minus 4/3 of the riser height, or</u> <u>2. The riser height shall be 15 inches (381 mm) minus 3/4 of the tread depth.</u> <p><u>AV104.2.1.4 Landing platforms.</u> The top tread and riser of stairways accessing lofts shall be constructed as a landing platform where the loft ceiling height is less than 6 feet 2 inches (1880 mm) where the stairway meets the loft. The landing platform shall be 18 inches to 22 inches (457 to 559 mm) in depth measured from the nosing of the landing platform to the edge of the loft, and 16 to 18 inches (406 to 457 mm) in height measured from the landing platform to the loft floor.</p> <p><u>AV104.2.1.4.1 Landing platform guards.</u> Guards at the open side of landing platforms shall comply with Section R312.1 or shall be at least as high as the loft guard; whichever is greater.</p> <p><u>AV104.2.1.5 Handrails.</u> Handrails shall comply with Section R311.7.8.</p> <p><u>AV104.2.1.6 Stairway guards.</u> Guards at open sides of stairways shall comply with Section R312.1.</p> <p><u>AV104.2.2 Ladders.</u> Ladders accessing lofts shall comply with Sections AV104.2.1 and AV104.2.2.</p> <p><u>AV104.2.2.1 Size and capacity.</u> Ladders accessing lofts shall have a rung width of not less than 12 inches (305 mm) and 10 inches (254 mm) to 14 inches (356 mm) spacing between rungs. Ladders shall be capable of supporting a 300 pound (75 kg) load on any rung. Rung spacing shall be uniform within 3/8-inch (9.5 mm).</p>		

*Note: These amendments are “proposed only” and have not been adopted by the Department of Community Affairs.

ACTION: A (Approve as Submitted); R (Approve as Revised); D (Disapprove); W (Withdrawn); CF (Carry Forward)

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION
		<p><u>AV104.2.2.2 Incline.</u> Ladders shall be installed at 70 to 80 degrees from horizontal.</p> <p><u>AV104.2.4 Ships ladders.</u> Ships ladders accessing lofts shall comply with Sections R311.7.12.1 and R311.7.12.2. The clear width at and below handrails shall be not less than 20 inches (508 mm). Compliant ship ladders may also access additional stories of a tiny house.</p> <p><u>AV104.2.5 Loft guards.</u> Loft guards shall be located along the open side of lofts. Loft guards shall not be less than 36 inches (914 mm) in height or one-half of the clear height to the ceiling, whichever is less, but no less than 18 inches.</p> <p style="text-align: center;"><u>SECTION AV105 EMERGENCY ESCAPE AND RESCUE OPENINGS</u></p> <p><u>AV105.1 General.</u> Tiny houses shall meet the requirements of Section R310 for emergency escape and rescue openings.</p> <p style="padding-left: 40px;"><u>Exception:</u> Egress roof access windows in lofts used as sleeping rooms shall be deemed to meet the requirements of Section R310 where installed such that the bottom of the opening is not more than 44 inches (1118 mm) above the loft floor, provided the egress roof access window complies with the minimum opening area requirements of Section R310.2.1.</p> <p style="text-align: center;"><u>SECTION AV106 SMOKE AND CARBON MONOXIDE DETECTORS</u></p> <p><u>AV106.1 SMOKE AND CARBON MONOXIDE DETECTORS.</u> Smoke and carbon monoxide detectors shall be installed as required in R313.1 and on the ceiling directly underneath any loft and just below the highest point of any loft.</p> <p>(Effective January 1, 2018)</p>		
7)	2012 IBC TABLE 1704.2	*Revise TABLE 1704.2 "MINIMUM SPECIAL INSPECTOR QUALIFICATIONS" of the current 2014 GA State Amendments to the 2012 IMC to read as follows:	Jimmy Cotty GRMCA	

*Note: These amendments are "proposed only" and have not been adopted by the Department of Community Affairs.

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION																																																																																																																							
		<table border="1"> <thead> <tr> <th colspan="4">TABLE 1704.2 MINIMUM SPECIAL INSPECTOR QUALIFICATIONS</th> </tr> <tr> <th rowspan="2">Category of Testing and Inspection</th> <th colspan="3">Minimum Qualifications (refer to key at end of Table)</th> </tr> <tr> <th>Shop Testing or Inspection</th> <th>Field Testing or Inspection</th> <th>Review Testing, Certification, & Lab Reports</th> </tr> </thead> <tbody> <tr> <td>Verify use of required design mix</td> <td></td> <td>A, I, J, H, C</td> <td></td> </tr> <tr> <td>Pre-stressed (pre-tensioned) concrete force application</td> <td>A, C, E</td> <td></td> <td></td> </tr> <tr> <td>Post-tensioned concrete force application</td> <td></td> <td>A, C, D</td> <td></td> </tr> <tr> <td>Review of in-situ concrete strength, prior to stressing of tendons in post-tensioned concrete and prior to removal of shores and forms from beams and structural slabs</td> <td></td> <td>A, C, D, H</td> <td></td> </tr> <tr> <td>Reinforcing steel weldability, reinforcing welding, weld filler material</td> <td></td> <td>C, F</td> <td></td> </tr> <tr> <td>Testing of welding of reinforcing steel</td> <td></td> <td>G</td> <td></td> </tr> <tr> <td colspan="4">1705.4 Masonry</td> </tr> <tr> <td>Verification of f'_m and f'_{AAC}</td> <td></td> <td>A, C, L, M</td> <td></td> </tr> <tr> <td>Mortar joint construction, grout protection and placement, materials proportion, type/size/location of reinforcement, structural elements, anchorage, and connectors</td> <td></td> <td>A, C, K</td> <td></td> </tr> <tr> <td>Sampling/testing of grout/mortar specimens</td> <td></td> <td>A, C, L, M</td> <td></td> </tr> <tr> <td>Observe preparation of masonry prisms for testing of compressive strength of masonry, f'_m and f'_{AAC}</td> <td></td> <td>A, C, K, L, M</td> <td></td> </tr> <tr> <td>Inspection of welding of reinforcing steel</td> <td></td> <td>C, F</td> <td></td> </tr> <tr> <td>Testing of welding of reinforcing steel</td> <td></td> <td>G</td> <td></td> </tr> <tr> <td colspan="4">1705.6 & 1804 Soils</td> </tr> <tr> <td>Observe site preparation, fill placement testing of compaction for compliance with the construction documents for the project</td> <td></td> <td>A, C, I, N</td> <td></td> </tr> <tr> <td>Observe test bearing materials below shallow foundations for ability to achieve design bearing capacity</td> <td></td> <td>A, C, N, I (Level III)</td> <td></td> </tr> <tr> <td>Review compaction testing for compliance with the construction documents for the project</td> <td></td> <td></td> <td>A</td> </tr> <tr> <td colspan="4">1705.5, 1705.10, 1705.11 & 1705.12 Wood Construction</td> </tr> <tr> <td>Observe structural panel sheathing, size of framing members, nail or staple diameter and length, number of fastener lines, and spacing of fastener lines and fasteners for compliance with construction documents for the project</td> <td></td> <td>A</td> <td></td> </tr> <tr> <td>Observe temporary and permanent truss member restraint/bracing, field gluing of elements. Observe bolting, anchoring or other fastening of: shear walls, diaphragms, drag struts, braces and hold-downs</td> <td></td> <td>A</td> <td></td> </tr> <tr> <td colspan="4">1705.7, 1705.8, 1705.9 & 1810 Pile and Pier Foundations</td> </tr> <tr> <td>Observe installation</td> <td></td> <td>A, N</td> <td></td> </tr> <tr> <td>Observe load tests</td> <td></td> <td>A</td> <td></td> </tr> <tr> <td colspan="4">1705.13 Sprayed Fire-Resistant Materials</td> </tr> <tr> <td>Observe surface conditions, application, average thickness and density of applied material, and cohesive/adhesive bond</td> <td></td> <td>A, C</td> <td></td> </tr> <tr> <td colspan="4">1705.14 Mastic and Intumescent Fire-Resistant Coatings</td> </tr> <tr> <td>Observe application compliance with AWCI 12-B</td> <td></td> <td>A, C</td> <td></td> </tr> </tbody> </table>	TABLE 1704.2 MINIMUM SPECIAL INSPECTOR QUALIFICATIONS				Category of Testing and Inspection	Minimum Qualifications (refer to key at end of Table)			Shop Testing or Inspection	Field Testing or Inspection	Review Testing, Certification, & Lab Reports	Verify use of required design mix		A, I, J, H, C		Pre-stressed (pre-tensioned) concrete force application	A, C, E			Post-tensioned concrete force application		A, C, D		Review of in-situ concrete strength, prior to stressing of tendons in post-tensioned concrete and prior to removal of shores and forms from beams and structural slabs		A, C, D, H		Reinforcing steel weldability, reinforcing welding, weld filler material		C, F		Testing of welding of reinforcing steel		G		1705.4 Masonry				Verification of f'_m and f'_{AAC}		A, C, L, M		Mortar joint construction, grout protection and placement, materials proportion, type/size/location of reinforcement, structural elements, anchorage, and connectors		A, C, K		Sampling/testing of grout/mortar specimens		A, C, L, M		Observe preparation of masonry prisms for testing of compressive strength of masonry, f'_m and f'_{AAC}		A, C, K, L, M		Inspection of welding of reinforcing steel		C, F		Testing of welding of reinforcing steel		G		1705.6 & 1804 Soils				Observe site preparation, fill placement testing of compaction for compliance with the construction documents for the project		A, C, I, N		Observe test bearing materials below shallow foundations for ability to achieve design bearing capacity		A, C, N, I (Level III)		Review compaction testing for compliance with the construction documents for the project			A	1705.5, 1705.10, 1705.11 & 1705.12 Wood Construction				Observe structural panel sheathing, size of framing members, nail or staple diameter and length, number of fastener lines, and spacing of fastener lines and fasteners for compliance with construction documents for the project		A		Observe temporary and permanent truss member restraint/bracing, field gluing of elements. Observe bolting, anchoring or other fastening of: shear walls, diaphragms, drag struts, braces and hold-downs		A		1705.7, 1705.8, 1705.9 & 1810 Pile and Pier Foundations				Observe installation		A, N		Observe load tests		A		1705.13 Sprayed Fire-Resistant Materials				Observe surface conditions, application, average thickness and density of applied material, and cohesive/adhesive bond		A, C		1705.14 Mastic and Intumescent Fire-Resistant Coatings				Observe application compliance with AWCI 12-B		A, C			
TABLE 1704.2 MINIMUM SPECIAL INSPECTOR QUALIFICATIONS																																																																																																																											
Category of Testing and Inspection	Minimum Qualifications (refer to key at end of Table)																																																																																																																										
	Shop Testing or Inspection	Field Testing or Inspection	Review Testing, Certification, & Lab Reports																																																																																																																								
Verify use of required design mix		A, I, J, H, C																																																																																																																									
Pre-stressed (pre-tensioned) concrete force application	A, C, E																																																																																																																										
Post-tensioned concrete force application		A, C, D																																																																																																																									
Review of in-situ concrete strength, prior to stressing of tendons in post-tensioned concrete and prior to removal of shores and forms from beams and structural slabs		A, C, D, H																																																																																																																									
Reinforcing steel weldability, reinforcing welding, weld filler material		C, F																																																																																																																									
Testing of welding of reinforcing steel		G																																																																																																																									
1705.4 Masonry																																																																																																																											
Verification of f'_m and f'_{AAC}		A, C, L, M																																																																																																																									
Mortar joint construction, grout protection and placement, materials proportion, type/size/location of reinforcement, structural elements, anchorage, and connectors		A, C, K																																																																																																																									
Sampling/testing of grout/mortar specimens		A, C, L, M																																																																																																																									
Observe preparation of masonry prisms for testing of compressive strength of masonry, f'_m and f'_{AAC}		A, C, K, L, M																																																																																																																									
Inspection of welding of reinforcing steel		C, F																																																																																																																									
Testing of welding of reinforcing steel		G																																																																																																																									
1705.6 & 1804 Soils																																																																																																																											
Observe site preparation, fill placement testing of compaction for compliance with the construction documents for the project		A, C, I, N																																																																																																																									
Observe test bearing materials below shallow foundations for ability to achieve design bearing capacity		A, C, N, I (Level III)																																																																																																																									
Review compaction testing for compliance with the construction documents for the project			A																																																																																																																								
1705.5, 1705.10, 1705.11 & 1705.12 Wood Construction																																																																																																																											
Observe structural panel sheathing, size of framing members, nail or staple diameter and length, number of fastener lines, and spacing of fastener lines and fasteners for compliance with construction documents for the project		A																																																																																																																									
Observe temporary and permanent truss member restraint/bracing, field gluing of elements. Observe bolting, anchoring or other fastening of: shear walls, diaphragms, drag struts, braces and hold-downs		A																																																																																																																									
1705.7, 1705.8, 1705.9 & 1810 Pile and Pier Foundations																																																																																																																											
Observe installation		A, N																																																																																																																									
Observe load tests		A																																																																																																																									
1705.13 Sprayed Fire-Resistant Materials																																																																																																																											
Observe surface conditions, application, average thickness and density of applied material, and cohesive/adhesive bond		A, C																																																																																																																									
1705.14 Mastic and Intumescent Fire-Resistant Coatings																																																																																																																											
Observe application compliance with AWCI 12-B		A, C																																																																																																																									

*Note: These amendments are "proposed only" and have not been adopted by the Department of Community Affairs.

ACTION: A (Approve as Submitted); R (Approve as Revised); D (Disapprove); W (Withdrawn); CF (Carry Forward)

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION																																											
		<table border="1"> <thead> <tr> <th colspan="4" data-bbox="604 245 1484 285">TABLE 1704.2 MINIMUM SPECIAL INSPECTOR QUALIFICATIONS</th> </tr> <tr> <td data-bbox="604 285 1087 451" rowspan="2">Category of Testing and Inspection</td> <td colspan="3" data-bbox="1087 285 1484 326">Minimum Qualifications (refer to key at end of Table)</td> </tr> <tr> <td data-bbox="1087 326 1247 451">Shop Testing or Inspection</td> <td data-bbox="1247 326 1392 451">Field Testing or Inspection</td> <td data-bbox="1392 326 1484 451">Review Testing, Certification, & Lab Reports</td> </tr> </thead> <tbody> <tr> <td colspan="4" data-bbox="604 451 1484 480">1705.15 Exterior Insulation and Finish Systems</td> </tr> <tr> <td data-bbox="604 480 1087 509">Inspect EIFS systems</td> <td data-bbox="1087 480 1247 509"></td> <td data-bbox="1247 480 1392 509">A, B, C, O</td> <td data-bbox="1392 480 1484 509"></td> </tr> <tr> <td colspan="4" data-bbox="604 509 1484 539">1705.1 Special Cases</td> </tr> <tr> <td data-bbox="604 539 1087 558">Work of unusual or special nature</td> <td data-bbox="1087 539 1247 558"></td> <td data-bbox="1247 539 1392 558">A, B, O</td> <td data-bbox="1392 539 1484 558"></td> </tr> <tr> <td data-bbox="604 558 1087 597">1705.16 Fire-Resistant Penetrations and Joints</td> <td colspan="3" data-bbox="1087 558 1484 597"><i>See Requirements of IBC Sections 1705.16.1 and 1705.16.2</i></td> </tr> <tr> <td data-bbox="604 597 1087 626">1705.17 Smoke Control</td> <td colspan="3" data-bbox="1087 597 1484 626"><i>See Requirements of IBC Section 1705.17.2</i></td> </tr> <tr> <td colspan="4" data-bbox="604 626 1484 656">1705.10, 1705.11 & 1705.12 Seismic and Wind Resistance</td> </tr> <tr> <td data-bbox="604 656 1087 695">Periodic inspection of fabrication, installation and/or anchorage of building systems and components</td> <td data-bbox="1087 656 1247 695"></td> <td data-bbox="1247 656 1392 695">A</td> <td data-bbox="1392 656 1484 695"></td> </tr> </tbody> </table> <p data-bbox="604 695 1484 1182">KEY:</p> <ul style="list-style-type: none"> A. Georgia Professional Engineer (GA PE) competent in the specific task area or graduate of accredited engineering/engineering technology program under the direct supervision of a GAPE. B. Georgia Registered Architect (GA RA) or graduate of accredited architecture/architecture technology program under the direction of a GA RA. C. International Code Council (ICC) Special Inspector Certification specific to the particular material and testing methodology applicable to each Category of Testing and Inspection listed in the table. D. Post-tensioning Institute (PTI) Certification, Level 2, bonded or unbonded as applicable. E. Pre-stressed Concrete Institute (PCI) Certified Inspector. F. American Welding Society (AWS) Certified Welding Inspector (CWI) or AWS Certified Associate Welding Inspector working under the direct on-site supervision of a CWI. G. American Society for Nondestructive Testing (ASNT) Level II certification, or a Level III certification if previously certified as a Level II in the particular material and testing methodology applicable to each Category of Testing and Inspection listed in the table. H. American Concrete Institute (ACI) Concrete Construction Special Inspector. I. National Institute for Certification in Engineering Technologies (NICET) Level II or higher certification specific to the particular material and testing methodology applicable to each Category of Testing and Inspection listed in the table. J. ACI Concrete Field Testing Technician with Grade 1 certification. K. Georgia Concrete and Products Association (GC&PA) – Masonry Association of Georgia (MAG) Masonry Construction Inspector Certification. L. National Concrete Masonry Association (NCMA) Concrete Masonry Testing Procedures certification. M. GC&PA – MAG Masonry Testing Technician certification. N. NICET Certified Engineering Technologist (CT). O. Other Qualified Special Inspector as approved by the Building Official. P. <u>American Concrete Institute (ACI) Strength Testing Technician</u> <p data-bbox="604 1182 1484 1331">Notes:</p> <ol style="list-style-type: none"> 1. <i>The Special Inspector shall meet one of the minimum qualifications listed for the applicable Category of Testing and Inspection.</i> 2. <i>Materials testing shall be done by an Approved Testing Agency meeting the requirements of IBC Section 1703 and ASTM E 329.</i> 3. <i>Concrete testing shall be done by an Approved Testing currently approved and in good standing with the Georgia State Finance & Investment Commission (GSFIC)</i> 	TABLE 1704.2 MINIMUM SPECIAL INSPECTOR QUALIFICATIONS				Category of Testing and Inspection	Minimum Qualifications (refer to key at end of Table)			Shop Testing or Inspection	Field Testing or Inspection	Review Testing, Certification, & Lab Reports	1705.15 Exterior Insulation and Finish Systems				Inspect EIFS systems		A, B, C, O		1705.1 Special Cases				Work of unusual or special nature		A, B, O		1705.16 Fire-Resistant Penetrations and Joints	<i>See Requirements of IBC Sections 1705.16.1 and 1705.16.2</i>			1705.17 Smoke Control	<i>See Requirements of IBC Section 1705.17.2</i>			1705.10, 1705.11 & 1705.12 Seismic and Wind Resistance				Periodic inspection of fabrication, installation and/or anchorage of building systems and components		A			
TABLE 1704.2 MINIMUM SPECIAL INSPECTOR QUALIFICATIONS																																															
Category of Testing and Inspection	Minimum Qualifications (refer to key at end of Table)																																														
	Shop Testing or Inspection	Field Testing or Inspection	Review Testing, Certification, & Lab Reports																																												
1705.15 Exterior Insulation and Finish Systems																																															
Inspect EIFS systems		A, B, C, O																																													
1705.1 Special Cases																																															
Work of unusual or special nature		A, B, O																																													
1705.16 Fire-Resistant Penetrations and Joints	<i>See Requirements of IBC Sections 1705.16.1 and 1705.16.2</i>																																														
1705.17 Smoke Control	<i>See Requirements of IBC Section 1705.17.2</i>																																														
1705.10, 1705.11 & 1705.12 Seismic and Wind Resistance																																															
Periodic inspection of fabrication, installation and/or anchorage of building systems and components		A																																													
		(Effective January 1, 2018)																																													

*Note: These amendments are “proposed only” and have not been adopted by the Department of Community Affairs.

ACTION: A (Approve as Submitted); R (Approve as Revised); D (Disapprove); W (Withdrawn); CF (Carry Forward)

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION
8) 2012 IBC	TABLE 2308.9.5	<p>*Revise TABLE 2308.9.5 'HEADER AND GIRDER SPANS FOR EXTERIOR BEARING WALLS' as follows:</p> <p>Table 2308.9.5 HEADER AND GIRDER SPANS FOR EXTERIOR BEARING WALLS (Maximum spans for Douglas fir-larch, Hem-Fir, Southern Pine and Spruce-Pine-Fir and required number of Jack Studs)</p> <p><i>Revise footnote b as follows:</i></p> <p>b. Spans are based on minimum design properties for No. 2 Grade lumber of Douglas fir-larch, hem-fir, <u>and spruce-pine-fir;</u> and No. 1 or better Grade lumber shall be used for <u>of</u> southern pine. <u>For No. 2 Grade southern pine the allowable spans shall be multiplied by 0.93.</u></p> <p><u>(Effective January 1, 2018)</u></p>	Paul Coats AWC	
9) 2012 IBC	TABLE 2308.9.6	<p>*Revise TABLE 2308.9.6 'HEADER AND GIRDER SPANS FOR INTERIOR BEARING WALLS' as follows:</p> <p>Table 2308.9.6 HEADER AND GIRDER SPANS FOR INTERIOR BEARING WALLS (Maximum spans for Douglas fir-larch, Hem-Fir, Southern Pine and Spruce-Pine-Fir and required number of Jack Studs)</p> <p><i>Revise footnote b as follows:</i></p> <p>b. Spans are based on minimum design properties for No. 2 Grade lumber of Douglas fir-larch, hem-fir, <u>and spruce-pine-fir;</u> and No. 1 or better Grade lumber shall be used for <u>of</u> southern pine. <u>For No. 2 Grade southern pine the allowable spans shall be multiplied by 0.93.</u></p> <p><u>(Effective January 1, 2018)</u></p>	Paul Coats AWC	
10) 2012 IPC	202	<p>*Revise Section 202 GENERAL DEFINITIONS to read as follows. :</p> <p>Shower Head. A shower head that allows a flow of no more than the average of 2.5 gallons of water per minute at 60 pounds per square inch of pressure.</p> <p><u>Shower Head. A shower head that allows a flow of no more than the average of 2.0 gallons of water per minute at 60 pounds per square inch of pressure and is listed to the EPA Partnership WaterSense Program water efficient shower head standard.</u></p> <p><u>(Effective January 1, 2018)</u></p>	Earnest Earn Cobb County	

*Note: These amendments are "proposed only" and have not been adopted by the Department of Community Affairs.

ACTION: A (Approve as Submitted); R (Approve as Revised); D (Disapprove); W (Withdrawn); CF (Carry Forward)

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION						
11) 2012 IPC	Table 604.4	<p>*Revise TABLE 604.4 'MAXIMUM FLOW RATES AND CONSUMPTION FOR PLUMBING FIXTURES AND FIXTURE FITTINGS' to read as follows:</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th colspan="2" style="text-align: center;">TABLE 604.4 MAXIMUM FLOW RATES AND CONSUMPTION FOR PLUMBING FIXTURES AND FIXTURE FITTINGS</th> </tr> <tr> <th style="text-align: center;">Plumbing Fixture Or Fixture Fitting</th> <th style="text-align: center;">Maximum Flow Rate or Quantity</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Shower head^a</td> <td style="text-align: center;">2.5 2.0 gpm at 60 psi</td> </tr> </tbody> </table> <p>Remainder of table and footnotes are unchanged.</p> <p><u>(Effective January 1, 2018)</u></p>	TABLE 604.4 MAXIMUM FLOW RATES AND CONSUMPTION FOR PLUMBING FIXTURES AND FIXTURE FITTINGS		Plumbing Fixture Or Fixture Fitting	Maximum Flow Rate or Quantity	Shower head ^a	2.5 2.0 gpm at 60 psi	Earnest Earn Cobb County	
TABLE 604.4 MAXIMUM FLOW RATES AND CONSUMPTION FOR PLUMBING FIXTURES AND FIXTURE FITTINGS										
Plumbing Fixture Or Fixture Fitting	Maximum Flow Rate or Quantity									
Shower head ^a	2.5 2.0 gpm at 60 psi									
12) 2012 IPC	424.10	<p>*Add new Section 424.10 'Pre-rinse spray valves' to read as follows:</p> <p><u>424.10 Pre-rinse spray valves.</u> All pre-rinse spray valves sold and installed in Georgia shall be labeled WaterSense and shall have a maximum flow rate of 1.28 gpm.</p> <p><u>(Effective January 1, 2018)</u></p>	Earnest Earn Cobb County							
13) 2012 IMC	202	<p>*Revise Section 202 GENERAL DEFINITIONS to add a new definition to read as follows:</p> <p><u>HIGH VOLUME LOW SPEED FAN.</u> A ceiling fan that circulates high volumes of air at low rotational speeds. Such fans are greater than 7 feet in diameter.</p> <p><u>(Effective January 1, 2018)</u></p>	Patrick Keal Big Ass Fans							
14) 2012 IMC	929	<p>*Add New Section 929 'HIGH VOLUME LOW SPEED FANS' to read as follows:</p> <p style="text-align: center;"><u>SECTION 929 HIGH VOLUME LOW SPEED FANS</u></p> <p><u>929.1 General.</u> Where provided, high volume low speed fans shall be tested and labeled in accordance with AMCA 230, listed and labeled in accordance with UL 507, an installed in accordance with the manufacturer's instructions.</p> <p><u>(Effective January 1, 2018)</u></p>	Patrick Keal Big Ass Fans							

*Note: These amendments are "proposed only" and have not been adopted by the Department of Community Affairs.

Note Proposed Amendments: (added text to the code is: underlined, deleted text to the code is: ~~struck through~~)

ITEM	SECTION	SUMMARY	PROPONENT	ACTION						
15) 2012 IMC	Chapter 15	<p>*Revise Chapter 15 'REFERENCED STANDARDS' to add the following new reference standards:</p> <p style="text-align: center;">CHAPTER 15 REFERENCED STANDARDS</p> <p>*Revise to add the following new referenced standard for AMCA:</p> <p style="text-align: center;"><u>AMCA</u> American Movement and Control Association International 30 West University Drive Arlington Heights, IL 60004</p> <hr/> <table border="0" style="width: 100%;"> <tr> <td style="width: 30%;">Standard Reference Number</td> <td style="width: 40%;">Title</td> <td style="width: 30%; text-align: right;">Reference in code section number</td> </tr> </table> <hr/> <p>230-15 Laboratory Methods of Testing Air Circulating Fans for Rating and Certification..... 929.1</p> <hr/> <p>*Revise to add the following new referenced standard for UL:</p> <p style="text-align: center;"><u>UL</u> Underwriters Laboratories, Inc. 333 Pfingsten Road Northbrook, IL 60062-2096</p> <hr/> <table border="0" style="width: 100%;"> <tr> <td style="width: 30%;">Standard Reference Number</td> <td style="width: 40%;">Title</td> <td style="width: 30%; text-align: right;">Reference in code section number</td> </tr> </table> <hr/> <p>507 9th Ed. 1999 Standard for Electric Fans 929.1</p> <hr/> <p><u>(Effective July 1, 2018)</u></p> <p style="text-align: center;">End of Report.</p>	Standard Reference Number	Title	Reference in code section number	Standard Reference Number	Title	Reference in code section number	Patrick Keal Big Ass Fans	
Standard Reference Number	Title	Reference in code section number								
Standard Reference Number	Title	Reference in code section number								

*Note: These amendments are "proposed only" and have not been adopted by the Department of Community Affairs.